

SHEET _____
SECTION _____



PRODUCT SUBMITTAL DATA

DUCT MARKERS

DESCRIPTION: Sturdy 4 mil vinyl with an aggressive permanent adhesive backing. Marker comes with detachable arrow to indicate flow in either direction. Clearly identifies duct work for easy tracking and maintenance.



Craftmark's Duct Markers will make HVAC Maintenance easy and safer and cost effective by clearly identifying duct work. Markers are available in two popular sizes-both come with detachable arrow to indicate flow in either direction.

FEATURES;

- Durable self-stick aggressive vinyl
- Indoor /outdoor grade
- Peel off liner for easy application
- 2 sizes to choose from
 - 2 1/4" x 16" with 1.25" Letters
 - 4" x 28" with 3.00" Letters
- Markers supplied with detachable arrow
- Custom legends & colors at no additional charge

STOCK LEGEND LIST						
SIZE	2 1/4" X 16"			4" X 28"		
LEGEND	Black on Yellow	White on Green	White on Blue	Black on Yellow	White on Green	White on Blue
EXHAUST	10881-DM	10882-DM	10883-DM	10774-DM	10775-DM	10766-DM
EXHAUST AIR	10884-DM	10885-DM	10886-DM	10776-DM	10777-DM	10767-DM
INTAKE	10887-DM	10888-DM	10889-DM	10778-DM	10779-DM	10768-DM
OUTSIDE AIR	10890-DM	10891-DM	10892-DM	10780-DM	10769-DM	10769A-DM
RELIEF	10893-DM	10894-DM	10895-DM	10781-DM	10782-DM	10770-DM
RELIEF AIR	10896-DM	10897-DM	10898-DM	10783-DM	10784-DM	10771-DM
RETURN AIR	10899-DM	10900-DM	10901-DM	10785-DM	10772-DM	10786-DM
SUPPLY AIR	10902-DM	10903-DM	10904-DM	10773-DM	10787-DM	10788-DM
ARROW	10905-DM	10906-DM	10907-DM	10795-DM	10796-DM	10797-DM

• STANDARD COLORS



DATE: ___ / ___ / ___ JOB: _____

CONTRACTOR: _____

DUCT MARKERS (Continued)

ADHESIVE: Permanent, Aggressive acrylic pressure sensitive adhesive. Sticks to most pipe and pipe covering materials.

SURFACE PREPARATION: Surface should be dry, oil free, dirt free and above the minimum application temperature.

SERVICE TEMPERATURE: -40°F to 200°F (-40°C to 93°C)

APPLICATION TEMPERATURE: Minimum application temperature of 50°F (10°C)

AVERAGE OUTDOOR DURABILITY: 5 years outdoor - mid continental U.S.

CHEMICAL RESISTANCE: VERY GOOD

MOISTURE RESISTANCE: EXCELLENT moisture resistance

ABRASION RESISTANCE: VERY GOOD abrasion resistance

GLOSS: 40 Gardner units (20° test)

STORAGE STABILITY: 2 years typical at 70°F (21°C) at 50% relative humidity

DATE: ___ / ___ / ___

JOB: _____

CONTRACTOR: _____