

SHEET \_\_\_\_\_  
 SECTION \_\_\_\_\_  
 \_\_\_\_\_  
 \_\_\_\_\_



# PRODUCT SUBMITTAL DATA

## DIRECTION FLOW - ARROW TAPE



**DESCRIPTION:** Indoor/Outdoor grade 4 mil vinyl is excellent for indicating flow direction along with Craftmark Pipe Markers.

**USE:** Direction Flow Arrow Tape can be used by itself to indicate flow direction as well as with Duramark Pipe Markers to comply 100% to ASME (ANSI) A13.1-2015

**COMPLIANCE:** ASME (ANSI A13.1-2015 Scheme for the Identification of Piping Systems).

Ansi Z535.1 Safety Color Codes.

**LEED Compliance:** This product is in compliance with Standards set forth by the South Coast Air Quality Management District (SCAQMD) Rule#1168 and the Green Seal Standard, GS-36 for Commercial Adhesives pertaining to Volatile Organic Compounds (VOC). Self-Stick adhesive backing contains less than 4.4g/Liter volatile organic compounds.

**Widths Available:** 1/2", 1", 2", 4", 6"

### •Tape Width Guideline

TAPE SIZE	USE WITH MARKER SIZE
1/2" x 30 yds	1 XSM
1" x 30 yds	1 SM
2" x 30 yds	1
4" x 30 yds	1LG
6" x 30 yds	1 XLG

### •STANDARD COLORS

- FLAMMABLE FLUIDS**  
SAFETY YELLOW
- POTABLE, COOLING, BOILER FEED & OTHER**  
SAFETY GREEN
- COMPRESSED AIR**  
SAFETY BLUE
- FIRE QUENCHING FLUIDS**  
SAFETY RED
- TOXIC & CORROSIVE FLUIDS**  
SAFETY ORANGE
- COMBUSTIBLE FLUIDS**  
SAFETY BROWN
- USER DEFINED**  
SAFETY PURPLE
- USER DEFINED**  
SAFETY WHITE
- USER DEFINED**  
SAFETY GRAY
- USER DEFINED**  
SAFETY BLACK

Pipe Diameter	Number of Bands Per Roll	Pipe Diameter	Number of Bands Per Roll
1"	344	6"	57
2"	172	7"	49
3"	115	8"	43
4"	86	9"	38
5"	68	10"	34

DATE: \_\_\_ / \_\_\_ / \_\_\_      JOB: \_\_\_\_\_

CONTRACTOR: \_\_\_\_\_

# DIRECTION FLOW - ARROW TAPE (Continued)

---

ADHESIVE: Permanent, Aggressive acrylic pressure sensitive adhesive. Sticks to most pipe and pipe covering materials.

---

SURFACE PREPARATION: Surface should be dry, oil free, dirt free and above the minimum application temperature.

---

SERVICE TEMPERATURE: -40°F to 200°F (-40°C to 93°C)

---

APPLICATION TEMPERATURE: Minimum application temperature of 50°F (10°C)

---

AVERAGE OUTDOOR DURABILITY: 5 years outdoor - mid continental U.S.

---

CHEMICAL RESISTANCE: VERY GOOD

---

MOISTURE RESISTANCE: EXCELLENT moisture resistance

---

ABRASION RESISTANCE: VERY GOOD abrasion resistance

---

GLOSS: 40 Gardner units (20° test)

---

STORAGE STABILITY: 2 years typical at 70°F (21°C) at 50% relative humidity

---

DATE: \_\_\_ / \_\_\_ / \_\_\_

JOB: \_\_\_\_\_

CONTRACTOR: \_\_\_\_\_