

SHEET _____
 SECTION _____



PRODUCT SUBMITTAL DATA

SPECMARK™ FIRE PROTECTION SNAP ON PIPE MARKER



DESCRIPTION: SPECMARK™ (sizes AA-F) are coiled printed sheet that are designed to snap around the pipe and stay there without need for adhesive. Sizes G-H are supplied flat and are installed with factory supplied UV stable black nylon ties.

USE: For marking all varieties of pipe-especially rusty, wet, damp, oily or especially dirty pipe. Also used as a labor saver on installations. Use indoor or outdoor.

COMPLIANCE: Complies 100% to ASME (ANSI) A13.1 2007 Scheme for the Identification of Piping Systems for color, color field width & letter size. Complies with ANSI Z535.1 Safety Color Code

Specmark™ Precoiled Plastic Markers save installation time and labor costs!

Craftmark's Specmark™ conform 100% to ASME (ANSI) 2007 Standard "Scheme for the Identification of Piping Systems". We use only the most durable materials and UV screen inks. These durable markers are used on wet, oily, cold, dirty, or rusty pipes, where pressure sensitives won't stick! No preparation of the pipe surface is required before application so valuable labor time is saved!

FEATURES

- Meets ASME (ANSI) 2007 Standard - 100%
- No pipe preparation necessary.
- 360° visibility.
- Installs quickly in new and existing facilities.
- Can be removed and re-used.
- Markers come with preprinted arrows.
- Choose from over 300 stock legends.
- Available in six standard coiled sizes.
- Sizes G-H supplied with Black Nylon, UV stabilized ties.
- Sizes to fit 3/8" thru 40"
- Coiled plastic is lightweight yet durable.
- Coiled marker snaps around pipe with ease.
- Heavy 20 mil vinyl on sizes A, B, G, H.
- Super Heavy-duty 30mil vinyl on sizes C, D, E, F
- Custom available with no set-up charges or hidden minimum orders. Order 1 with no set-up charge!

• STANDARD COLORS

FIRE QUENCHING FLUIDS

• SPECMARK FIRE PROTECTION Snap-On Application Guide

<p>STYLE A</p> <ul style="list-style-type: none"> • For pipe diameters 3/4" - 1" 8" marker width, 1/2" letters 	
<p>STYLE B</p> <ul style="list-style-type: none"> • For pipe diameters 1 1/8" - 2 3/8" 8" marker width, 3/4" letters 	
<p>STYLE C</p> <ul style="list-style-type: none"> • For pipe diameters 2 1/2" - 3 1/4" 12" marker width, 1 1/4" letters 	
<p>STYLE D</p> <ul style="list-style-type: none"> • For pipe diameters 3 3/8" - 4 1/2" 12" marker width, 1 1/4" letters 	
<p>STYLE E</p> <ul style="list-style-type: none"> • For pipe diameters 4 5/8" - 5 7/8" 12" marker width, 1 1/4" letters 	
<p>STYLE F</p> <ul style="list-style-type: none"> • For pipe diameters 6" - 8" 12" marker width, 1 1/4" letters 	
<p>STYLE G</p> <ul style="list-style-type: none"> • For pipe diameters 8" - 10" 24" marker width, 2 1/2" letters 	
<p>STYLE H</p> <ul style="list-style-type: none"> • For pipe diameters over 10" 32" marker width, 3 1/2" letters 	

DATE: ___ / ___ / ___ JOB: _____

CONTRACTOR: _____

SPECMARK™ FIRE PROTECTION SNAP ON PIPE MARKER (Continued)

ADHESIVE: N/A - No need for adhesive

SURFACE PREPARATION: NONE NEEDED - A huge labor saver!!

SERVICE TEMPERATURE: Sizes A-H -40°F to 180°F (-40°C to 82°C)

APPLICATION TEMPERATURE: N/A

AVERAGE OUTDOOR DURABILITY: 5-8 years average. Results vary based on locations, environmental conditions & varies with background color.

CHEMICAL RESISTANCE: Excellent resistance to most petroleum solvents and low aliphatic alcohols.

MOISTURE RESISTANCE: EXCELLENT

ABRASION RESISTANCE: EXCELLENT

GLOSS: 60 units (20° test)

STORAGE STABILITY: Indefinite storage & shelf life when stored at 70°F (21°C) and relative humidity.

DATE: ___ / ___ / ___

JOB: _____

CONTRACTOR: _____
