

SHEET _____
 SECTION _____



PRODUCT SUBMITTAL DATA

ROLLMARK V SELF-STICK ROLLFORM PIPE MARKER



DESCRIPTION: Self-adhesive rolls of pre-printed stock and custom pipe markers. With acrylic pressure sensitive adhesive backing sturdy 4 mil vinyl.

USE: Use to identify piping systems. Designed for all pipe marking jobs.

COMPLIANCE: Complies with ASME (ANSI) A13.1 2007 Scheme for the Identification of Piping Systems for color, color field width & letter size.

Craftmark's Rollmark V is ideal for all pipe marking jobs. Easy to use Rollmark V comes with pre-slit arrows so they can be used to indicate flow in either direction. Rollmark V comes with 50 legends and 50 arrows per roll. Available in 3 sizes to fit most pipe jobs up to 6" diameter.

FEATURES

- Ultra-durable self-stick vinyl for indoor/outdoor use.
- Available in 3 sizes.
- Full 50 legends / 50 arrows per roll.
- 85 stock legends.
- Custom available.
- Meets ASME (ANSI) A13.1 2007

• ROLLMARK V Application Guide

Style RMSM
 1" x 8" - 3/4" Letters



Style RMLG
 2" x 12" - 1 1/4" Letters



Style RMXLG
 4" x 24" - 3" Letters



• STANDARD COLORS

FLAMMABLE FLUIDS

POTABLE, COOLING, BOILER FEED & OTHER

COMPRESSED AIR

FIRE QUENCHING FLUIDS

TOXIC & CORROSIVE FLUIDS

COMBUSTIBLE FLUIDS

USER DEFINED

USER DEFINED

USER DEFINED

USER DEFINED

DATE: ___ / ___ / ___

JOB: _____

CONTRACTOR: _____

ROLLMARK V SELF-STICK ROLLFORM PIPE MARKER (Continued)

ADHESIVE: Permanent, aggressive acrylic pressure sensitive adhesive. Sticks to most pipe and pipe covering materials.

SURFACE PREPARATION: Surface should be dry, oil free, dirt free and above the minimum application temperature.

SERVICE TEMPERATURE: -40°F to 200°F (-40°C to 93°C)

APPLICATION TEMPERATURE: Minimum application temperature of 50°F (10°C)

AVERAGE OUTDOOR DURABILITY: 5 years outdoor - mid continental U.S.

CHEMICAL RESISTANCE: VERY GOOD

MOISTURE RESISTANCE: EXCELLENT MOISTURE RESISTANCE

ABRASION RESISTANCE: VERY GOOD ABRASION RESISTANCE

GLOSS: 40 Gardner units (20° test)

STORAGE STABILITY: 2 years typical at 70°F (21°C) at 50% relative humidity.

DATE: ___ / ___ / ___

JOB: _____

CONTRACTOR: _____